

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

2015

© COPYRIGHT 2000

BY TE CONNECTIVITY





ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
J3		REVISED PER PCN-24-200566	19FEB2024	CO	CB
J4		REVISED PER PCN-24-213773	02JUL2024	HD	CB
K		REVISED PER PCN-24-219306	29AUG2024	CO	CB
L		REVISED PER PCN-25-233228	18DEC2024	RK	CB



6. RECEPTACLE IS SUPPLIED WITH DUST CAP (2415-001-2405).

5. NOTED DIMENSION DOES NOT INCLUDE GROMMET PROTRUSION.

4. MATERIAL: RECEPTACLE HOUSING: PA66 GF10 (BLACK)
RETAINER RING: PA66 GF10 (GREEN, GRAY, BLUE)
GROMMET: SILICONE (ORANGE-RED)

3. SEE 0425-021-0000 APPLICATION SPECIFICATION
A. RECOMMENDED WIRE INSULATION RANGE
B. CONTACT REMOVAL TOOLS
C. RECOMMENDED MOUNTING HOLE & PANEL THICKNESS
D. MOUNTING HARDWARE & MOUNTING TORQUE.

2. THIS RECEPTACLE MATES WITH HDP26-24-XXP/SX-XXXX PLUG
X = SEAL TYPE (N,T,E)
XX = INSERT ARRANGEMENT
XXXX = MODIFICATION

1. SEE CUSTOMER DRAWING, 0425-014-2400 FOR AVAILABLE INSERT ARRANGEMENTS AND PART NUMBERS.


NOTES:

8. LOCATIONS FOR TRACEABILITY WITNESS MARKS ONLY

7. DATE CODE: IDENTIFIES THE YEAR, MONTH, DAY AND HOUR OF ASSEMBLY.
YEAR: FIRST AND SECOND DIGITS. (14 = 2014)
MONTH: THRID DIGIT, EXCLUDING I. A = JAN., B = FEB., C = MARCH.... (K = OCTOBER)
DAY: FOURTH AND FIFTH DIGITS (14 = 14th DAY)
HOUR: SIXTH AND SEVENTH DIGITS (11 = 11AM)

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
INCHES[mm]



MATERIAL



TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ±
1 PLC ±
2 PLC ±
3 PLC ±.015 [0.38]
4 PLC ±
ANGLES ±0°30'0"

FINISH

N/A

DWN 03MAR2000

STEVE BEARD

CHK 04FEB2004

JUNE LIM

APVD 16JAN2004

STEVE BEARD

PRODUCT SPEC

0425-021-0000

APPLICATION SPEC



WEIGHT

Customer Drawing



TE Connectivity

NAME
RECEPTACLE, THREADED
SIZE 24
HDP SERIES

SIZE CAGE CODE DRAWING NO RESTRICTED TO

A3 4AFU8 C-HDP24-24-XXP/SX

SCALE 2:1 SHEET 1 OF 1 REV L