

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

2015

© COPYRIGHT 2010

BY TE CONNECTIVITY





ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
B1		REVISED PER ECO-16-013285	08SEP2016	DD	DM
B2		REVISED PER PCN-24-200566	16FEB2024	CO	CB
C		REVISED PER PCN-24-219306	29AUG2024	CO	CB
D		REVISED PER PCN-25-233228	18DEC2024	RK	CB



6. PART MODIFICATION:
3 SIZE 4: 4 AWG [21.0-25.0 mm²] AND 4 SIZE 16.

5. RECEPTACLE IS SUPPLIED WITH DUST CAP (2415-001-2405). 7 DATE CODE: IDENTIFIES THE YEAR, MONTH, DAY AND HOUR OF ASSEMBLY.

4 NOTED DIMENSION DOES NOT INCLUDE GROMMET PROTRUSION.

3 MATERIAL: RECEPTACLE HOUSING: PA66 GF10 (BLACK)
RETAINER RING: PA66 GF10 (GREEN, GRAY, BLUE)
GROMMET: SILICONE (ORANGE-RED)

2 SEE 0425-021-0000 APPLICATION SPECIFICATION
A. RECOMMENDED WIRE INSULATION RANGE
B. CONTACT REMOVAL TOOLS
C. RECOMMENDED MOUNTING HOLE & PANEL THICKNESS
D. MOUNTING HARDWARE & MOUNTING TORQUE.

1. THIS RECEPTACLE MATES WITH HDP26-24-7SX-XXXX PLUG
X = SEAL TYPE (N,T,E)
XXXX = MODIFICATION

NOTES:

YEAR: FIRST AND SECOND DIGITS. (14 = 2014)
MONTH: THIRD DIGIT, EXCLUDING I. A = JAN., B = FEB., C = MARCH.... (K = OCTOBER)
DAY: FOURTH AND FIFTH DIGITS (14 = 14th DAY)
HOUR: SIXTH AND SEVENTH DIGITS (11 = 11AM)

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES[mm]	TOLERANCES UNLESS OTHERWISE SPECIFIED:
	0 PLC ± 1 PLC ± 2 PLC ± 3 PLC ±.015 [0.38] 4 PLC ± ANGLES ±0°30'0"
MATERIAL 3	FINISH N/A

DWN 01APR2010 ILINA GRANTCHAROVA	CHK 21JUL2010 JAIME C. APOSTOL	APVD 12JUL2010 STEVE BEARD
PRODUCT SPEC		
0425-021-0000		
APPLICATION SPEC 2		
WEIGHT 48.28g		
Customer Drawing		

NAME		RECEPTACLE, THREADED SIZE 24, -C038 MOD HDP SERIES	
SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	4AFU8	C-HDP24-24-7PN-C038	-
SCALE 2:1		SHEET 1 OF 1	REV D

TE

TE Connectivity